







BARGE "HFL - 3077" HINES FURLONG LINE

INNAGE TABLE

3 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 4756

Table with columns for depth (0 FT. to 15 FT.) and fractional increments (1/4, 1/2, 3/4). Each cell contains capacity values in barrels.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 12/17/2010

\* CAPACITY BELOW STRIKE POINT.

REFERENCE GAUGE HEIGHT : 17'-2 3/4" (TO RIM OF 2" DIAMETER BALL VALVE LOCATED ON EXPANSION DOME)

REISSUED : 05/19/2021 (TO REFLECT CHANGE OF BARGE NAME AND OWNERSHIP) BARGE NOT RESTRAPPED

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Signature

BUREAU VERITAS NORTH AMERICA





BARGE "HFL - 3077"
HINES FURLONG LINE
INNAGE TABLE

SLOP
(FWD)

HULL NO. 4756

Table with columns for length (0 FT. to 15 FT.) and rows for depth (0, 1/4, 1/2, 3/4). Each cell contains a numerical value representing the innage.

CAPACITIES GIVEN IN WHOLE U.S. GALLONS

REFERENCE GAUGE HEIGHT : 5'-7 1/2"

STRAPPED: 12/17/2010
REISSUED : 05/19/2021 (TO REFLECT CHANGE OF BARGE NAME AND OWNERSHIP) BARGE NOT RESTRAPPED

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Bureau Veritas North America logo and name



BARGE "HFL - 3077"
HINES FURLONG LINE
INNAGE TABLE

SLOP
(AFT)

HULL NO. 4756

Table with columns for length (0 FT. to 15 FT.) and sub-columns for depth (IN, 1/4, 1/2, 3/4). Rows represent length intervals (0-1, 1-2, etc.).

CAPACITIES GIVEN IN WHOLE U.S. GALLONS

REFERENCE GAUGE HEIGHT : 5'-7 1/2"

STRAPPED: 12/17/2010
REISSUED : 05/19/2021 (TO REFLECT CHANGE OF BARGE NAME AND OWNERSHIP) BARGE NOT RESTRAPPED

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

BUREAU VERITAS NORTH AMERICA



BUREAU VERITAS

# BARGE "HFL - 3077"

## HINES FURLONG LINE

HULL NO. 4756

### CORRECTION TABLE FOR TRIM AFT.

### FOR OUTAGE GAUGES ONLY

TRIM	TANKS NO. 1 PORT OR STAR.	TANKS NO. 2 PORT OR STAR.	TANKS NO. 3 PORT OR STAR.
0'-6"	(+) 0' - 1"	(+) 0' - 1"	(-) 0' - 1"
1'-0"	(+) 0' - 2"	(+) 0' - 2"	(-) 0' - 2"
1'-6"	(+) 0' - 3"	(+) 0' - 3"	(-) 0' - 3"
2'-0"	(+) 0' - 4"	(+) 0' - 4"	(-) 0' - 4"
2'-6"	(+) 0' - 5"	(+) 0' - 5"	(-) 0' - 5"
3'-0"	(+) 0' - 6"	(+) 0' - 6"	(-) 0' - 6"
3'-6"	(+) 0' - 7"	(+) 0' - 7"	(-) 0' - 7"
4'-0"	(+) 0' - 8"	(+) 0' - 8"	(-) 0' - 8"
4'-6"	(+) 0' - 9"	(+) 0' - 9"	(-) 0' - 9"
5'-0"	(+) 0' - 9 7/8"	(+) 0' - 10"	(-) 0' - 9 7/8"

NOTE: FOR TRIM FWD., REVERSE SIGNS.

NOTE: IF LIQUID SURFACE TOUCHES TANK BOTTOM OR DECK WHEN GAUGED, TRIM CORRECTIONS ARE NOT ACCURATE.

NOTE: FOR "INNAGE" GAUGES, REVERSE SIGNS.

**NOTE: FOR 2" DIAMETER BALL VALVE ONLY (CLOSED GAUGING)**

DATE: 05/19/21

BY: 

**BUREAU VERITAS NORTH AMERICA**